FIND A DEALER

SCHEDULE A WALKAROUND

REQUEST A

Primary Menu

COMPACT TRACK LOADERS

SKID STEERS

INDUSTRIES

BUYING TOOLS

SUPPORT

ABOUT

OVERVIEW

FEATURES

SPECS

GALLERY

RT-25

WARRANTY

BUILD & PRICE

FEATURES

Get More From Less



POWER

This versatile machine offers an industrial 25-horsepower Perkins diesel engine. Operators can use that power to achieve maximum productivity by moving around quickly (5.1 mph top speed), digging and lifting more. The engine is turbocharged so it can output its full horsepower even at high elevations.

PERFORMANCE

The RT-25 features a 4-foot machine width, a rated operating capacity of 665

FIND A DEALER

Primary Menu

COMPACT TRACK LOADERS

BUYING TOOLS

SKID STEERS

INDUSTRIES

BUILD & PRICE

SUPPORT

ABOUT

OVERVIEW

FEATURES

SPECS

GALLERY

RT-25

WARRANTY

BUILD & PRICE

Loader Arms	Radial	Features Pilot Hydraulic Joystick Control, Manual Quick Attach			stick	
Operating Weight	3755 lbs				ick Attach	
Rated Operating Capacity @ 35%	665 lbs	Mayimaum Cyclems	Dunna	2000:		
Rated Operating Capacity @ 50%	950 lbs	Maximum System Pressure		3000 psi		
Ground Pressure	3.1 psi	Auxiliary Hydraulic Connections 2				
Engine Power	24.7 hp	Auxiliary Pump Flow		11.3 gpm		
Tipping Load	1900 lbs					
Max. Travel Speed	5.1 mph	ELECTRICAL SYSTEM				
Height to Bucket Pin	101 in.	Features Upgradeable Wiring Harnes		Harnoos		
Maximum Dump Angle at Full Height	40 Degrees	reatures	Upgradeable Wiring Harness		паннеѕѕ	
Rear Angle of Departure	55 Degrees	Normal Charge			12 V	
Bucket Roll Back at Ground Level	18 Degrees	Battery			525 CCA	
Ground Clearance: Unloaded	10 in.	Alternator Charging System			65 Amp	
Overall Length with Bucket	114 in.	Port Outlet (Inside Operators Cab)		ab)	1 - 12V	

ENGINE

Features Diesel 3-cylinder, Perkins 403J-

17T, Engine-Driven Fan, Anti-Freeze Filled Radiator Cooling System, Dual Stage Intake Air

Cleaner, Engine Block Heater

Emissions Controls Meets All Emission Standards

for Markets: USA, Canada, Latin America, South America,

Central America and Caribbean

OPERATOR STATION

Features ROPS, Basic Seat w/ 2, Horn,

Backup Alarm

Loader Control Right-Hand Pilot Hydraulic

> Joystick Controls Loader Tilt/Lift, With Intermittent

Control of Auxiliary Hydraulics

Drive Control Left-Hand Pilot Hydraulic

Joystick Controls, Hand

Throttle Engine Speed Control

Gauges Fuel, Engine Temperature, Hour

https://www.asvi.com/compact-track-loaders/rt-25/#loader-section-specs

FIND A DEALER

REQUEST A

Primary Menu

COMPACT TRACK LOADERS

SKID STEERS

INDUSTRIES

BUILD & PRICE

BUYING TOOLS

SUPPORT **OVERVIEW** ABOUT

FEATURES

SPECS

GALLERY

RT-25

WARRANTY

BUILD & PRICE

Features

Dual Hydraulic Drive Motors, 2

Independent Torsion Axle Suspension, Duo Cone Front &

Rear

1 Rear Facing Light

Track Width

11 in

Length of Track on the

Ground Contact Area

55 in

Ground

1210 in²

Roller Wheels

12 high density

polyurethane

Roller Wheel Diameter

10 in

SERVICE CAPACITY

Fuel Tank

10 gal

Hydraulic Tank

4 gal


Engine Coolant


1.6 gal

Engine Oil (Including Filter)

6.3 quarts

DIMENSIONS





- A. Full Length 114 in.
- B. Hinge Pin Height 101 in.
- C. Machine Height 72.5 in.
- D. Width 48 in.
- E. Ground Clearance 10 in.